



## PRODUCT INFORMATION BULLETIN

**Date:** May 30, 2025  
**Number:** 53025  
**Division:** Genie®  
**Product Family:** Residential Gate Operators  
**Product Series:** Slide Gate  
**To:** All Genie Professional Line Wholesalers, Dealers, and Installers  
**Re:** New Product Release: Model GRSL24V

---

The Genie Company is pleased to announce the release of the model GRSL24V operator for residential slide gate applications. Starting June 2<sup>nd</sup>, this product will be available for order from your source for Genie operator products!

### Specifications

- Rated for use on horizontal slide gates up to 25ft wide and 850lbs.
- 50% duty cycle, up to 120 cycles per day
- 115VAC, field adjustable to 230VAC, or solar power (with optional solar kit)
- Operating temperature range -20° to +60°C (-40° to +60°C with optional heater)
- UL 325 Listed - Class I, II

### Features & Benefits

- Dual line backlit LCD display for easy setup
- Fully adjustable speed profile for precise control over gate opening and closing
- Timer to close settable from 1 to 240 seconds
- Four monitored safety inputs
- Built-in 7-day timer, no need to purchase additional hardware
- Wired primary/secondary for bi-parting gate applications (wireless available as an option)
- Advanced 315/390Mhz radio receiver stores up to 250 Intellicode® transmitters with unique IDs
- Aladdin Connect® ready (with optional Wi-Fi board)
- Direct drive power transmission for superior reliability and reduced maintenance
- #40 chain for maximum durability and consistent performance

### Packaged Operator

- P/N: OPRSL24V
- Each packaged operator contains:
  - (2) 12V 7Ah batteries
  - (1) Retro-reflective photo eye kit
  - (1) 5ft 10k Ohm monitored edge with mounting channel
  - (2) 3-button 315/390Mhz Intellicode® transmitters

