



PRODUCT INFORMATION BULLETIN

Date: July 17, 2015
Number: 8893
Division: Genie®
Product Family: Commercial Operators
Product Series: GCL Standard and Heavy Duty
To: All Genie Professional Line Wholesalers, Dealers and Installers
Re: New Feature: Timer Close On-Board

A software enhancement has been made to add Timer Close as a standard feature on the main board of standard and heavy duty operator models. This feature provides the operator with an automatic door closing feature with a user selectable time delay, adjustable from 2 seconds to 5 minutes (in increments of 2 seconds) using the LCD display.

The final version of software went into production on March 2, 2015 as a running change. To determine if an operator has the new Timer Close software:

UL Listed Models: GSX T / J / H and GHX T / H
Serial Number of the operator will be: 15062 or greater
Board Version # will be: Ver: 2.10.3 or greater

Non-Ventilated, Fan-Cooled, NEMA 4, or NEMA 4X Models: GSX T / J / H and GHX T / H
Serial Number of the operator will be: 15133 or greater
Board Version # will be: Ver: 2.10.3 or greater

This On-board Timer Close feature does require that a monitored safety device be installed and enabled in the calibration settings in order for momentary contact close operation (to meet UL 325-2010 requirements).

For operators with previous software versions, the Timer Close Expansion Module must be used. In general, the Timer Close Expansion Module (TCM), part number OPABTCGX.S, can still be added to *any* standard or heavy duty unit to provide the timer close functionality or other expanded capabilities, such as a pre-close warning or monitored edge applications.

If you have any questions, please contact Technical Support Services at 800-843-4084, option 4.